

保温付二重管重量表

本管・SUS304～外装管・STK400									
本管 ステンレス鋼管 SUS304 Sch10s			外装管 構造用鋼管 STK400			保温材 硬質ウレタン	本管内水	合計	
呼び径	外径 * 管厚 mm mm	重量 kg/m	外径 * 管厚 mm mm	重量 kg/m	重量 kg/m	重量 kg/m	重量 kg/m	重量 kg/m	
50A	60.5 * 2.8	4.02	216.3 * 4.5	23.47	1.85	2.37	31.71		
	60.5 * 2.8	4.02	216.3 * 5.8	30.07	1.80	2.37	38.26		
	60.5 * 2.8	4.02	267.4 * 6.0	38.63	2.90	2.37	47.92		
	60.5 * 2.8	4.02	267.4 * 6.6	42.40	2.87	2.37	51.66		
65A	76.3 * 3.0	5.48	216.3 * 4.5	23.47	1.75	3.88	34.58		
	76.3 * 3.0	5.48	216.3 * 5.8	30.07	1.70	3.88	41.13		
	76.3 * 3.0	5.48	267.4 * 6.0	38.63	2.80	3.88	50.79		
	76.3 * 3.0	5.48	267.4 * 6.6	42.40	2.77	3.88	54.53		
80A	89.1 * 3.0	6.43	216.3 * 4.5	23.47	1.65	5.42	36.97		
	89.1 * 3.0	6.43	216.3 * 5.8	30.07	1.60	5.42	43.52		
	89.1 * 3.0	6.43	267.4 * 6.0	38.63	2.70	5.42	53.18		
	89.1 * 3.0	6.43	267.4 * 6.6	42.40	2.67	5.42	56.92		
	89.1 * 3.0	6.43	318.5 * 6.0	46.18	4.05	5.42	62.08		
	89.1 * 3.0	6.43	318.5 * 6.9	52.96	4.00	5.42	68.81		
100A	114.3 * 3.0	8.32	216.3 * 4.5	23.47	1.41	9.21	42.41		
	114.3 * 3.0	8.32	216.3 * 5.8	30.07	1.36	9.21	48.96		
	114.3 * 3.0	8.32	267.4 * 6.0	38.63	2.46	9.21	58.62		
	114.3 * 3.0	8.32	267.4 * 6.6	42.40	2.43	9.21	62.36		
	114.3 * 3.0	8.32	318.5 * 6.0	46.18	3.81	9.21	67.52		
	114.3 * 3.0	8.32	318.5 * 6.9	52.96	3.76	9.21	74.25		
	114.3 * 3.0	8.32	355.6 * 6.4	55.05	4.92	9.21	77.50		
	114.3 * 3.0	8.32	355.6 * 7.9	67.65	4.83	9.21	90.01		
125A	139.8 * 3.4	11.55	267.4 * 6.0	38.63	2.15	13.89	66.22		
	139.8 * 3.4	11.55	267.4 * 6.6	42.40	2.12	13.89	69.96		
	139.8 * 3.4	11.55	318.5 * 6.0	46.18	3.51	13.89	75.13		
	139.8 * 3.4	11.55	318.5 * 6.9	52.96	3.45	13.89	81.85		
	139.8 * 3.4	11.55	355.6 * 6.4	55.05	4.62	13.89	85.11		
	139.8 * 3.4	11.55	355.6 * 7.9	67.65	4.52	13.89	97.61		
150A	165.2 * 3.4	13.71	267.4 * 6.0	38.63	1.79	19.71	73.84		
	165.2 * 3.4	13.71	267.4 * 6.6	42.40	1.76	19.71	77.58		
	165.2 * 3.4	13.71	318.5 * 6.0	46.18	3.14	19.71	82.74		
	165.2 * 3.4	13.71	318.5 * 6.9	52.96	3.09	19.71	89.47		
	165.2 * 3.4	13.71	355.6 * 6.4	55.05	4.25	19.71	92.72		
	165.2 * 3.4	13.71	355.6 * 7.9	67.65	4.16	19.71	105.23		
200A	216.3 * 4.0	21.16	318.5 * 6.0	46.18	2.22	34.08	103.64		
	216.3 * 4.0	21.16	318.5 * 6.9	52.96	2.17	34.08	110.37		
	216.3 * 4.0	21.16	355.6 * 6.4	55.05	3.33	34.08	113.62		
	216.3 * 4.0	21.16	355.6 * 7.9	67.65	3.24	34.08	126.13		
	216.3 * 4.0	21.16	406.4 * 6.4	63.05	5.10	34.08	123.39		
	216.3 * 4.0	21.16	406.4 * 7.9	77.54	4.98	34.08	137.76		
250A	267.4 * 4.0	26.25	355.6 * 6.4	55.05	2.17	52.85	136.32		
	267.4 * 4.0	26.25	355.6 * 7.9	67.65	2.07	52.85	148.82		
	267.4 * 4.0	26.25	406.4 * 6.4	63.05	3.93	52.85	146.08		
	267.4 * 4.0	26.25	406.4 * 7.9	77.54	3.82	52.85	160.46		
	267.4 * 4.0	26.25	457.2 * 6.4	71.06	5.94	52.85	156.10		
	267.4 * 4.0	26.25	457.2 * 7.9	87.42	5.81	52.85	172.33		
300A	318.5 * 4.5	35.20	406.4 * 6.4	63.05	2.52	75.23	176.00		
	318.5 * 4.5	35.20	406.4 * 7.9	77.54	2.41	75.23	190.38		
	318.5 * 4.5	35.20	457.2 * 6.4	71.06	4.53	75.23	186.02		
	318.5 * 4.5	35.20	457.2 * 7.9	87.42	4.40	75.23	202.25		
	318.5 * 4.5	35.20	508.0 * 6.4	79.07	6.78	75.23	196.28		
	318.5 * 4.5	35.20	508.0 * 7.9	97.31	6.64	75.23	214.38		
350A	355.6 * 5.0	43.67	457.2 * 6.4	71.06	3.35	93.81	211.89		
	355.6 * 5.0	43.67	457.2 * 7.9	87.42	3.22	93.81	228.12		
	355.6 * 5.0	43.67	508.0 * 6.4	79.07	5.60	93.81	222.15		
	355.6 * 5.0	43.67	508.0 * 7.9	97.31	5.46	93.81	240.25		

本管・SUS304～外装管・SUS304 SDP

本管 ステンレス鋼管 SUS304 Sch10s		外装管 スパイラル管 SUS304			保温材 硬質ウレタン	本管内水	合計
呼び径	外径 * 管厚 mm mm	重量 kg/m	外径 * 管厚 mm mm	重量 kg/m	重量 kg/m	重量 kg/m	重量 kg/m
50A	60.5 * 2.8	4.02	200.0 * 0.5	3.11	1.41	2.37	10.91
	60.5 * 2.8	4.02	200.0 * 0.6	3.73	1.41	2.37	11.53
	60.5 * 2.8	4.02	250.0 * 0.5	3.89	2.29	2.37	12.57
	60.5 * 2.8	4.02	250.0 * 0.6	4.66	2.29	2.37	13.34
65A	76.3 * 3.0	5.48	200.0 * 0.5	3.11	1.33	3.88	13.80
	76.3 * 3.0	5.48	200.0 * 0.6	3.73	1.32	3.88	14.41
	76.3 * 3.0	5.48	250.0 * 0.5	3.89	2.21	3.88	15.46
	76.3 * 3.0	5.48	250.0 * 0.6	4.66	2.20	3.88	16.22
80A	89.1 * 3.0	6.43	200.0 * 0.5	3.11	1.24	5.42	16.20
	89.1 * 3.0	6.43	200.0 * 0.6	3.73	1.24	5.42	16.82
	89.1 * 3.0	6.43	250.0 * 0.5	3.89	2.12	5.42	17.86
	89.1 * 3.0	6.43	250.0 * 0.6	4.66	2.12	5.42	18.63
	89.1 * 3.0	6.43	300.0 * 0.5	4.66	3.20	5.42	19.71
	89.1 * 3.0	6.43	300.0 * 0.6	5.59	3.19	5.42	20.63
100A	114.3 * 3.0	8.32	200.0 * 0.5	3.11	1.04	9.21	21.68
	114.3 * 3.0	8.32	200.0 * 0.6	3.73	1.04	9.21	22.30
	114.3 * 3.0	8.32	250.0 * 0.5	3.89	1.92	9.21	23.34
	114.3 * 3.0	8.32	250.0 * 0.6	4.66	1.92	9.21	24.11
	114.3 * 3.0	8.32	300.0 * 0.5	4.66	3.00	9.21	25.19
	114.3 * 3.0	8.32	300.0 * 0.6	5.59	2.99	9.21	26.11
	114.3 * 3.0	8.32	350.0 * 0.6	6.53	4.26	9.21	28.32
	114.3 * 3.0	8.32	350.0 * 0.8	8.70	4.25	9.21	30.48
125A	139.8 * 3.4	11.55	250.0 * 0.5	3.89	1.67	13.89	31.00
	139.8 * 3.4	11.55	250.0 * 0.6	4.66	1.66	13.89	31.76
	139.8 * 3.4	11.55	300.0 * 0.5	4.66	2.74	13.89	32.84
	139.8 * 3.4	11.55	300.0 * 0.6	5.59	2.74	13.89	33.77
	139.8 * 3.4	11.55	350.0 * 0.6	6.53	4.01	13.89	35.98
	139.8 * 3.4	11.55	350.0 * 0.8	8.70	4.00	13.89	38.14
150A	165.2 * 3.4	13.71	250.0 * 0.5	3.89	1.36	19.71	38.67
	165.2 * 3.4	13.71	250.0 * 0.6	4.66	1.36	19.71	39.44
	165.2 * 3.4	13.71	300.0 * 0.5	4.66	2.44	19.71	40.52
	165.2 * 3.4	13.71	300.0 * 0.6	5.59	2.43	19.71	41.44
	165.2 * 3.4	13.71	350.0 * 0.6	6.53	3.71	19.71	43.66
	165.2 * 3.4	13.71	350.0 * 0.8	8.70	3.69	19.71	45.81
200A	216.3 * 4.0	21.16	300.0 * 0.5	4.66	1.67	34.08	61.57
	216.3 * 4.0	21.16	300.0 * 0.6	5.59	1.67	34.08	62.50
	216.3 * 4.0	21.16	350.0 * 0.6	6.53	2.94	34.08	64.71
	216.3 * 4.0	21.16	350.0 * 0.8	8.70	2.93	34.08	66.87
	216.3 * 4.0	21.16	400.0 * 0.6	7.46	4.41	34.08	67.11
	216.3 * 4.0	21.16	400.0 * 0.8	9.95	4.40	34.08	69.59
250A	267.4 * 4.0	26.25	300.0 * 0.5	4.66	0.70	52.85	84.46
	267.4 * 4.0	26.25	300.0 * 0.6	5.59	0.70	52.85	85.39
	267.4 * 4.0	26.25	350.0 * 0.6	6.53	1.97	52.85	87.60
	267.4 * 4.0	26.25	350.0 * 0.8	8.70	1.96	52.85	89.76
	267.4 * 4.0	26.25	400.0 * 0.6	7.46	3.44	52.85	90.00
	267.4 * 4.0	26.25	400.0 * 0.8	9.95	3.43	52.85	92.48
300A	318.5 * 4.5	35.20	400.0 * 0.6	7.46	2.26	75.23	120.15
	318.5 * 4.5	35.20	400.0 * 0.8	9.95	2.25	75.23	122.63
	318.5 * 4.5	35.20	450.0 * 0.6	8.40	3.93	75.23	122.76
	318.5 * 4.5	35.20	450.0 * 0.8	11.19	3.91	75.23	125.53
	318.5 * 4.5	35.20	500.0 * 0.6	9.33	5.79	75.23	125.55
	318.5 * 4.5	35.20	500.0 * 0.8	12.44	5.77	75.23	128.64
350A	355.6 * 5.0	43.67	450.0 * 0.6	8.40	2.94	93.81	148.82
	355.6 * 5.0	43.67	450.0 * 0.8	11.19	2.93	93.81	151.60
	355.6 * 5.0	43.67	500.0 * 0.6	9.33	4.80	93.81	151.61
	355.6 * 5.0	43.67	500.0 * 0.8	12.44	4.79	93.81	154.71

本管・水道配水用PE～外装管・STK400

本管 水道配水用ポリエチレンパイプ			外装管 構造用鋼管 STK400			保温材 硬質ウレタン	本管内水	合計
呼び径	外径 * 管厚 mm mm	重量 kg/m	外径 * 管厚 mm mm	重量 kg/m	重量 kg/m	重量 kg/m	重量 kg/m	
50A	63.0 * 5.8	1.07	216.3 * 4.5	23.47	1.84	2.07	28.45	
	63.0 * 5.8	1.07	216.3 * 5.8	30.07	1.79	2.07	35.00	
	63.0 * 5.8	1.07	267.4 * 6.0	38.63	2.89	2.07	44.66	
	63.0 * 5.8	1.07	267.4 * 6.6	42.40	2.86	2.07	48.40	
80A	90.0 * 8.2	2.17	216.3 * 4.5	23.47	1.64	4.25	31.53	
	90.0 * 8.2	2.17	216.3 * 5.8	30.07	1.59	4.25	38.08	
	90.0 * 8.2	2.17	267.4 * 6.0	38.63	2.69	4.25	47.74	
	90.0 * 8.2	2.17	267.4 * 6.6	42.40	2.66	4.25	51.48	
	90.0 * 8.2	2.17	318.5 * 6.0	46.18	4.05	4.25	56.65	
	90.0 * 8.2	2.17	318.5 * 6.9	52.96	3.99	4.25	63.37	
100A	125.0 * 11.4	4.19	216.3 * 4.5	23.47	1.29	8.20	37.15	
	125.0 * 11.4	4.19	216.3 * 5.8	30.07	1.24	8.20	43.70	
	125.0 * 11.4	4.19	267.4 * 6.0	38.63	2.34	8.20	53.36	
	125.0 * 11.4	4.19	267.4 * 6.6	42.40	2.31	8.20	57.10	
	125.0 * 11.4	4.19	318.5 * 6.0	46.18	3.69	8.20	62.26	
	125.0 * 11.4	4.19	318.5 * 6.9	52.96	3.64	8.20	68.99	
150A	180.0 * 16.4	8.69	267.4 * 6.0	38.63	1.55	17.02	65.89	
	180.0 * 16.4	8.69	267.4 * 6.6	42.40	1.52	17.02	69.63	
	180.0 * 16.4	8.69	318.5 * 6.0	46.18	2.90	17.02	74.79	
	180.0 * 16.4	8.69	318.5 * 6.9	52.96	2.85	17.02	81.52	
	180.0 * 16.4	8.69	355.6 * 6.4	55.05	4.01	17.02	84.77	
	180.0 * 16.4	8.69	355.6 * 7.9	67.65	3.91	17.02	97.27	
200A	250.0 * 22.7	16.71	318.5 * 6.0	46.18	1.48	32.88	97.25	
	250.0 * 22.7	16.71	318.5 * 6.9	52.96	1.43	32.88	103.98	
	250.0 * 22.7	16.71	355.6 * 6.4	55.05	2.59	32.88	107.23	
	250.0 * 22.7	16.71	355.6 * 7.9	67.65	2.50	32.88	119.74	
	250.0 * 22.7	16.71	406.4 * 6.4	63.05	4.36	32.88	117.00	
	250.0 * 22.7	16.71	406.4 * 7.9	77.54	4.24	32.88	131.37	

本管・水道配水用PE～外装管・SUS304 SDP

本管 水道配水用ポリエチレンパイプ			外装管 スパイラル管 SUS304			保温材 硬質ウレタン	本管内水	合計
呼び径	外径 * 管厚 mm mm	重量 kg/m	外径 * 管厚 mm mm	重量 kg/m	重量 kg/m	重量 kg/m	重量 kg/m	
50A	63.0 * 5.8	1.07	200.0 * 0.5	3.11	1.40	2.07	7.65	
	63.0 * 5.8	1.07	200.0 * 0.6	3.73	1.40	2.07	8.27	
	63.0 * 5.8	1.07	250.0 * 0.5	3.89	2.28	2.07	9.31	
	63.0 * 5.8	1.07	250.0 * 0.6	4.66	2.28	2.07	10.08	
80A	90.0 * 8.2	2.17	200.0 * 0.5	3.11	1.24	4.25	10.77	
	90.0 * 8.2	2.17	200.0 * 0.6	3.73	1.23	4.25	11.38	
	90.0 * 8.2	2.17	250.0 * 0.5	3.89	2.12	4.25	12.43	
	90.0 * 8.2	2.17	250.0 * 0.6	4.66	2.11	4.25	13.19	
100A	125.0 * 11.4	4.19	200.0 * 0.5	3.11	0.94	8.20	16.44	
	125.0 * 11.4	4.19	200.0 * 0.6	3.73	0.94	8.20	17.06	
	125.0 * 11.4	4.19	250.0 * 0.5	3.89	1.82	8.20	18.10	
	125.0 * 11.4	4.19	250.0 * 0.6	4.66	1.82	8.20	18.87	
150A	180.0 * 16.4	8.69	250.0 * 0.5	3.89	1.16	17.02	30.76	
	180.0 * 16.4	8.69	250.0 * 0.6	4.66	1.16	17.02	31.53	
	180.0 * 16.4	8.69	300.0 * 0.5	4.66	2.24	17.02	32.61	
	180.0 * 16.4	8.69	300.0 * 0.6	5.59	2.23	17.02	33.53	
	180.0 * 16.4	8.69	350.0 * 0.6	6.53	3.51	17.02	35.75	
	180.0 * 16.4	8.69	350.0 * 0.8	8.70	3.49	17.02	37.90	
200A	250.0 * 22.7	16.71	300.0 * 0.5	4.66	1.06	32.88	55.31	
	250.0 * 22.7	16.71	300.0 * 0.6	5.59	1.05	32.88	56.23	
	250.0 * 22.7	16.71	350.0 * 0.6	6.53	2.32	32.88	58.44	
	250.0 * 22.7	16.71	350.0 * 0.8	8.70	2.31	32.88	60.60	
	250.0 * 22.7	16.71	400.0 * 0.6	8.40	3.79	32.88	61.78	
	250.0 * 22.7	16.71	400.0 * 0.8	11.19	3.78	32.88	64.56	

本管・下水道用PE～外装管・外装管・STK400

本管 下水道用ポリエチレンパイプ			外装管 構造用鋼管 STK400			保温材 硬質ウレタン	本管内水	合計
呼び径	外径 * 管厚 mm mm	重量 kg/m	外径 * 管厚 mm mm	重量 kg/m	重量 kg/m	重量 kg/m	重量 kg/m	
50A	63.0 * 4.7	0.89	216.3 * 4.5	23.47	1.84	2.26	28.46	
	63.0 * 4.7	0.89	216.3 * 5.8	30.07	1.79	2.26	35.01	
	63.0 * 4.7	0.89	267.4 * 6.0	38.63	2.89	2.26	44.67	
	63.0 * 4.7	0.89	267.4 * 6.6	42.40	2.86	2.26	48.41	
80A	90.0 * 6.7	1.81	216.3 * 4.5	23.47	1.64	4.61	31.53	
	90.0 * 6.7	1.81	216.3 * 5.8	30.07	1.59	4.61	38.08	
	90.0 * 6.7	1.81	267.4 * 6.0	38.63	2.69	4.61	47.74	
	90.0 * 6.7	1.81	267.4 * 6.6	42.40	2.66	4.61	51.48	
	90.0 * 6.7	1.81	318.5 * 6.0	46.18	4.05	4.61	56.65	
	90.0 * 6.7	1.81	318.5 * 6.9	52.96	3.99	4.61	63.37	
100A	125.0 * 9.2	3.43	216.3 * 4.5	23.47	1.29	8.92	37.11	
	125.0 * 9.2	3.43	216.3 * 5.8	30.07	1.24	8.92	43.66	
	125.0 * 9.2	3.43	267.4 * 6.0	38.63	2.34	8.92	53.32	
	125.0 * 9.2	3.43	267.4 * 6.6	42.40	2.31	8.92	57.06	
	125.0 * 9.2	3.43	318.5 * 6.0	46.18	3.69	8.92	62.22	
	125.0 * 9.2	3.43	318.5 * 6.9	52.96	3.64	8.92	68.95	
150A	180.0 * 13.3	7.13	267.4 * 6.0	38.63	1.55	18.48	65.79	
	180.0 * 13.3	7.13	267.4 * 6.6	42.40	1.52	18.48	69.53	
	180.0 * 13.3	7.13	318.5 * 6.0	46.18	2.90	18.48	74.69	
	180.0 * 13.3	7.13	318.5 * 6.9	52.96	2.85	18.48	81.42	
	180.0 * 13.3	7.13	355.6 * 6.4	55.05	4.01	18.48	84.67	
	180.0 * 13.3	7.13	355.6 * 7.9	67.65	3.91	18.48	97.17	
200A	250.0 * 18.4	13.71	318.5 * 6.0	46.18	1.48	35.70	97.07	
	250.0 * 18.4	13.71	318.5 * 6.9	52.96	1.43	35.70	103.80	
	250.0 * 18.4	13.71	355.6 * 6.4	55.05	2.59	35.70	107.05	
	250.0 * 18.4	13.71	355.6 * 7.9	67.65	2.50	35.70	119.56	
	250.0 * 18.4	13.71	406.4 * 6.4	63.05	4.36	35.70	116.82	
	250.0 * 18.4	13.71	406.4 * 7.9	77.54	4.24	35.70	131.19	

本管・下水道用PE～外装管・SUS304 SDP

本管 下水道用ポリエチレンパイプ			外装管 スパイラル管 SUS304			保温材 硬質ウレタン	本管内水	合計
呼び径	外径 * 管厚 mm mm	重量 kg/m	外径 * 管厚 mm mm	重量 kg/m	重量 kg/m	重量 kg/m	重量 kg/m	
50A	63.0 * 4.7	0.89	200.0 * 0.5	3.11	1.40	2.26	7.66	
	63.0 * 4.7	0.89	200.0 * 0.6	3.73	1.40	2.26	8.28	
	63.0 * 4.7	0.89	250.0 * 0.5	3.89	2.28	2.26	9.32	
	63.0 * 4.7	0.89	250.0 * 0.6	4.66	2.28	2.26	10.09	
80A	90.0 * 6.7	1.81	200.0 * 0.5	3.11	1.24	4.61	10.77	
	90.0 * 6.7	1.81	200.0 * 0.6	3.73	1.23	4.61	11.38	
	90.0 * 6.7	1.81	250.0 * 0.5	3.89	2.12	4.61	12.43	
	90.0 * 6.7	1.81	250.0 * 0.6	4.66	2.11	4.61	13.19	
100A	125.0 * 9.2	3.43	200.0 * 0.5	3.11	0.94	8.92	16.40	
	125.0 * 9.2	3.43	200.0 * 0.6	3.73	0.94	8.92	17.02	
	125.0 * 9.2	3.43	250.0 * 0.5	3.89	1.82	8.92	18.06	
	125.0 * 9.2	3.43	250.0 * 0.6	4.66	1.82	8.92	18.83	
150A	180.0 * 13.3	7.13	250.0 * 0.5	3.89	1.16	18.48	30.66	
	180.0 * 13.3	7.13	250.0 * 0.6	4.66	1.16	18.48	31.43	
	180.0 * 13.3	7.13	300.0 * 0.5	4.66	2.24	18.48	32.51	
	180.0 * 13.3	7.13	300.0 * 0.6	5.59	2.23	18.48	33.43	
	180.0 * 13.3	7.13	350.0 * 0.6	6.53	3.51	18.48	35.65	
	180.0 * 13.3	7.13	350.0 * 0.8	8.70	3.49	18.48	37.80	
200A	250.0 * 18.4	13.71	300.0 * 0.5	4.66	1.06	35.70	55.13	
	250.0 * 18.4	13.71	300.0 * 0.6	5.59	1.05	35.70	56.05	
	250.0 * 18.4	13.71	350.0 * 0.6	6.53	2.32	35.70	58.26	
	250.0 * 18.4	13.71	350.0 * 0.8	8.70	2.31	35.70	60.42	
	250.0 * 18.4	13.71	400.0 * 0.6	8.40	3.79	35.70	61.60	
	250.0 * 18.4	13.71	400.0 * 0.8	11.19	3.78	35.70	64.38	